

## ETNA 2

### Next Generation of Web Based, Cost Effective, Strong Motion Accelerographs

Kinematics' **ETNA** accelerograph established the world's standard for strong motion recording for almost two decades with more than 6000 installations worldwide. The **ETNA 2** represents the next generation of ETNA-class accelerographs offering NEW and cost effective, web based monitoring capabilities paired with another Kinematics' established world standard, the exemplary **EpiSensor** accelerometer.

The ETNA 2 is easy to use since it was designed around the Rockhound application software first implemented on the Basalt instruments and continued now on the new Obsidian instruments.

ETNA 2 offers the most essential accelerograph features supporting a wide range of earthquake monitoring applications in a small, lightweight, and simple to use package. If you are interested in Earthquake Early Warning, in structural monitoring, in aftershocks surveys or even in induced earthquake monitoring related to oil and gas, and geothermal fluid injection activities, the ETNA 2 is the right product for you.

And for those whose job it is to maintain large number of stations, we implemented Streamlined Station Maintenance (SSM) that allows you to use your browser to log maintenance activities such as software updates, site inspections, or battery replacements right on the unit. These logs can be automatically uploaded to your data center for archiving, reducing paper work in the field, and eliminating human error.



## FEATURES

- 3 sensor channels with an internal EpiSensor triaxial deck
- 24-bit Delta Sigma converter, one per channel
- Matched to Kinematics outstanding EpiSensor accelerometer performance
- Built-in GPS and PTP timing options
- Record and communicate multiple sample rates
- Earthquake Early Warning low latency 0.1s packets ready
- Multiple telemetry protocols: ORB natively or public domain Earthworm and SeedLink
- Streamlined Station Maintenance (SSM)
- Data offloaded automatically to removable thumb drive connected to the USB host port. Parallel recording (mirroring) data on an external USB thumb drive.
- Wireless communications via USB based Wi-Fi or cellular modem
- State-of-health monitoring, including input and system voltages, internal temperature, communication link diagnostics, available storage
- IP Security through SSH and SSL
- Reverse voltage protection and self resettable fuses
- System Status LEDs
- Surviving temporary immersion at 1 m depth (rated IP67)
- Designed for RoHS Compliance and easy re-cycling
- Designed for the lowest Total Cost of Ownership (TCO)



## SPECIFICATIONS

### Sensor

Type: Triaxial EpiSensor force balance accelerometers, orthogonally oriented, internal  
 Full scale range: User selectable at  $\pm 1g$ ,  $\pm 2g$  or  $\pm 4g$   
 Bandwidth: DC to 200 Hz  
 Dynamic range: 155 dB+  
 Offset: Factory set, software re-zeroing

### Digitizer

Channels: 3 sensor channels for the internal sensors  
 Dynamic range:  $\sim 130$  dB at 100sps (defined as RMS clip to RMS shorted-input noise) or  $\sim 139$  dB at 100 sps (defined as full scale peak to peak to RMS shorted-input noise)  
 Primary sample rates: 1, 10, 20, 50, 100, 200, 250, 500 sps  
 Secondary sample rates: A second lower sample rate can be selected from the primary sample rates above

Acquisition modes: Continuous (ring buffer) and triggered  
 Calibration & test: Pulse and Sensor Response Test

### Trigger

Trigger selection: Independently selected for each channel Internal Threshold, selectable from 0.01% to 100% of full scale or STA/LTA algorithm  
 Trigger: Internal and network trigger votes with arithmetic combination  
 Trigger voting: Internal and network trigger votes with arithmetic combination

### Timing

Type: Oscillator digitally locked to GPS or to PTP master  
 Timing: accuracy:  $< 1$  microseconds of UTC with GPS locked

### Storage

Data storage: Internal SDHC Card, 16 GB  
 System storage: Internal SDHC Card, 2 GB  
 Data: Offloaded automatically to removable thumb drive connected to the USB host port. Parallel recording (mirroring) data on an external USB thumb drive.  
 File formats: MiniSEED, EVT, and ASCII  
 USB drive file system: FAT32

### Interfaces and Digital Control

Interfaces: 1 x Ethernet 10/100BaseT  
 (M12 connectors) 1 x USB 2.0 Device Port for data access  
 1 x USB 2.0 Host Port for peripherals  
 1 x RS-232 for factory use only  
 Relays: 2 x SPDT relays, software configurable  
 LEDs: System, power and event status, Ethernet Link

### Communications

Ethernet interface: Real Time Telemetry (Multiple destinations TCP/IP Protocol), web server for parameter setup, event retrieval via FTP/SFTP; supports Point of Contact (POC) name service  
 Modem: External, cellular or POTS, connected via the USB 2.0 Host interface; consult factory for details  
 Protocols: Real-time data streaming via Antelope compatible ORB server or via public domain SEEDLink and Earthworm protocols  
 State-Of-Health: Input voltage, Super Capacitor voltage, Time synchronization, internal temperature, available storage  
 Low latency: 1s and 0.1s data packets i.e. for EEWS applications  
 Data visualization: Waveform Viewer for continuous waveform display and File Viewer for triggered event display; consult factory for other support software

### Power Requirements

Consumption:  $< 3W$  operational  
 Voltage range: 9-28 VDC  
 Protections: Reverse voltage, over/under voltage, self resettable fuses

### Physical

Mounting: Central bolt, 3 adjustable feet, air bubble leveling  
 Dimensions: 6" x 6" x 3" (15cm x 15 cm x 7.5cm)  
 Volume: 1.6 liters  
 Weight: 3.3 lbs. (1.5 kg)

### Environmental

Temperature range:  $-20^{\circ}$  to  $70^{\circ}C$  operational  
 Humidity: 0-100% RH (non-condensing)  
 Enclosure rating: IP67

Specifications subject to change without notice



中国区代理: 博来银赛科技(北京)有限公司  
 地址: 北京市顺义区裕曦路绿地启航国际11号院2号楼802室  
 电话: 010-8882 9199 传真: 010-8882 9299  
 网址: www.broadinsight.cn  
 邮箱: sales@broadinsight.cn